



670 New York Street
Memphis, TN 38104
www.chemicar.com

Tel: 800.261.7976
Fax: 901.274.8816
sales@chemicar.com

FOLLEX FINE LINE TAPE

DESCRIPTION:

This resilient PVC film substrate provides good solvent resistance, high conformability and a smooth sharp mask-off edge. The blended rubber based adhesive system offers high temperature resistance through bake cycles up to 311°F for 45 minutes.

ADHESIVE:

- Rubber blend pressure sensitive adhesive
- Providing high tack

CARRIER:

- 0.13 mm Poly vinyl chloride film
- Color Blue

APPLICATIONS:

- | | |
|--|-----------------------------|
| Car | Industry |
| ▪ OEM Automotive high temp mask | ▪ Fineline Masking |
| ▪ Aftermarket autobody, fineline masking | ▪ Outdoor use up to 72 hrs. |

TECHNICAL DETAILS:

Adhesion to steel-----	16.42 N/100mm
Adhesion to steel (20 min. dwell)-----	26.3 N/100mm
Tensile Strength-----	210 N/100mm
Elongation (at break)-----	100%
Service temperature range-----	0°C-> + 311°F
Solvent resistance-----	Very Good

APPLICATION:

Temperature between +59°F and + 86°F. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hrs at 72°F.

STORAGE & SHELF LIFE:

Clean and dry in a well ventilated area, preferably at a temperature between 50°F and 86°F. Stored under these conditions shelf life will be a minimum of 1 year.

SIZES:

FOL 72: 1/8 x 36y FOL 73: 1/4 x 36y FOL 74: 3/8 x 36y FOL 75: 1/2 x 36y

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. The manufacturer cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.