



670 New York Street  
Memphis, TN 38104  
[www.chemicar.com](http://www.chemicar.com)

Tel: 800.261.7976  
Fax: 901.274.8816  
sales@chemicar.com

## FOLLEX FLEECE WIRE HARNESS TAPE (FOL 66)

### **DESCRIPTION:**

This textile protective tape has especially been designed for manual cable harness production typical for the passenger compartment. It is abrasive resistant, noise reducing, resistant to aging and not self-extinguishing. Provides abrasion protection and prevents rattles and squeaks.

### **ADHESIVE:**

- Rubber adhesive

### **CARRIER:**

- PET fleece textile

### **COLOR:**

- Black

### **APPLICATIONS:**

- Manual cable harness for the passenger compartment-headliner-doors-trunk of vehicles.
- Not for use in engine compartment.

### **TECHNICAL DETAILS:**

Total Thickness----- 0.3 mm  
Adhesive Strength----- >1,5 N/cm  
Elongation at break----- 10-25%  
Tensile Strength----- 40 N/cm  
Temperature Resistance----- 110°C/230°F

### **APPLICATION:**

Temperature between +50°F and + 122°F. Surface must be clean and free from dust and grease. Avoid touching exposed adhesive surface of the tape, as this impairs the performance. Pressure sensitive adhesive must be applied with a maximum pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hrs at 23°C/75°F.

### **STORAGE & SHELF LIFE:**

Clean and dry in a well ventilated area, preferably at a temperature between 50°F and 86°F. Stored under these conditions shelf life will be a minimum of 1 year.

### **SIZES:**

FOL 66 0.75 inches x 27.34 yards

*The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. The manufacturer cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.*